

VACUUM CLEANERS - DUST ETRACTORS - PROFESSIONAL TOOLINGS

GS 1/25 OPT M TC SP13

POWER MAX

WATER LIFT

AIRFLOW

TANK CAPACITY

1200

2300 mmH₂0

200 m³/h

25

EXCLUSIVE FEATURES

- INNOVATIVE GASKET
- STRONG HOOKS
- NEW ECO-BAG
- DETACHABLE TANK AND SOLID CART
- TELECONTROL
- M FILTER CLASSIFICATION
- MULTISTAGE FILTRATION
- DOUBLE STAGE MOTOR WITH HIGH PERFORMANCE
- AUTOMATIC FILTER CLEANING SYSTEM "SP13"
- ELECTROSTATIC DISSIPATION
- RELIABLE CONSTRUCTION FOR INTENSIVE USE





MOST FREQUENTLY USE

CONSTRUCTION

HARDWARE CUSTOMER

INDUSTRY

AUTOMOTIVE

INNOVATIONS





SPECS



DETACHABLE TANK



ELECTRICAL FILTER SHAKER



ADDITIONAL SOCKET FOR POWER TOOL (TC) WITH AUTOMATIC START/STOP

TECHNICAL DATA

GS 1/25 OPT M TC SP13

PERFORMANCE

Usage		Dry
Motor		1
Power	W	1000-1200 max
Voltage	V	220-240
Water lift	mmH_2O	2300
Airflow	m³/h	200
Gross capacity/material	l	25/Steel
Cable length	m	8
Filtering surface	cm²	5000
Diameter of accessories	mm	36
Dimensions (lxwxh)	mm	550x650x1100
Weight (without accessories)	kg	16

STANDARD EQUIPMENT

POLY CARTRIDGE 5.000 cm²

MICROFIBER BAG CLASS M





ACCESSORIES KIT Ø36 MM COMPOSED OF:

CONDUCTIVE FLEXIBLE HOSE 4 m Ø36 mm

PLASTIC TUBE 50 CM (2 PCS) CONDUCTIVE WAND WITH DUST TOOL Ø36 mm

AIR REGULATOR Ø36 mm













ROUND BRUSH Ø36 mm







OPTIONAL ACCESSORIES

(10 PCS)

MICROFIBER BAG CLASS M COMPLETE CAP FOR INLET COVER FOR DRILL (FOR SAFE DISPOSAL)







ELECTRO-PNEUMATIC KIT Ø29 mm



ELECTRIC KIT Ø29 mm



ELECTRO-PNEUMATIC KIT Ø36 mm

